

PRO S Series

10~20kVA 3/1 phase Tower UPS



Power range

10~20kVA



Operation

1P/1P,3P/1P,online double conversion



Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



Characteristics

- Intelligent battery management.
- 3-level topology, high performance and efficiency.
- Online double conversion, full digital control.
- Output PF=1,high load adaptability.
- Wide range of input voltage tolerance.
- Adapt to half-wave load.
- Auto fault waveform recording.
- Self-aging function to save test energy.

Model	PRO S 010	PRO S 015	PRO S 020
Rate Power	10kVA	15kVA	20kVA
Cold start	Default output 50/60Hz		
Input voltage range	190~499VAC(L-L)		
Input power factor	≥0.99		
Frequency range	40-70Hz		
Output frequency	50/60Hz,self adaption		
Output power factor	1		
Rate output	220/230/240VAC		
Load regulation	±1%		
Output THDu	≤1%,Linear load ; ≤3%,non-linear load according to IEC62040-3		
Transfer time-INV to BYP	0ms		
Efficiency- normal mode	Up to 95%		
Efficiency- ECO mode	98%		
Noise (1 meter)	<55dB	<62dB	<62dB
Overload (normal mode)	110%: 10mins; 125%: 1min; 150%: 30 seconds		
Battery Model	External batteries, 16-24 settable		
Battery Quantity	External batteries, 16-24 settable		
Battery Max charging	5A		
Battery Rate voltage	Default 192VDC, settable		
Crest factor	3:1		
Standard	RS232, RS485, EPO		
Option	AS400, SNMP card, Parallel kit, USB, 12A charger, Air filter, Single Input kit, Maintenance bypass kit		
Dimension,(W*D*H)mm	190*564*500		
Weight (kg)	30		